



# LUMEN X<sup>+</sup>

CELLINK   
A BICO COMPANY

| Volumetric 


---

Construct microscopic features  
with speed, fidelity and precision.

## Lumen X+™

The Lumen X+, powered by Volumetric, leverages digital light processing (DLP) printing to offer users high resolution, high throughput and high fidelity, enhancing applications in microfluidics, cell-laden hydrogels, macroporous structures and more. Designed to bioprint vasculature with visible blue light (405 nm), the Lumen X+ gives you a powerful advantage in achieving complex branching and tapering of vessels.


Lumen X+ is being launched through an exciting partnership with CELLINK and Volumetric, a Texas-based startup. We have combined our expertise to optimize the technology for all your bioprinting needs.






## The Printing Principle


The Lumen X+ builds solid hydrogels by beginning with a droplet of light-sensitive, liquid PhotoInk™ in a vat. An industrial blue-light projector exposes a series of images onto the vat, like a slideshow. The areas of the droplet that are exposed will crosslink and solidify into a single layer. The build platform moves up to allow each layer to stack and build the part.





.....




Alveolar cluster (6 x 6 x 9 mm) – Gas exchange network with fluid channels and air inlets. Smallest channel diameter is approximately 250  $\mu\text{m}$ .





.....

Multiple alveolar sac models (11 x 20 x 15 mm) – Combined into a cluster with common inputs and outputs. Smallest channel diameter is approximately 250  $\mu\text{m}$ .






Vessel exchanger (15 x 12 x 6 mm) – Two unique vessel networks that intertwine for the exchange of gas, fluids and nutrients. Average channel diameter is 350  $\mu\text{m}$ .



.....


Hilbert space-filling curve (15 x 10 x 8 mm) – A mathematical curve converted into a 400  $\mu\text{m}$  diameter channel, demonstrating the ability to construct a tortuous channel.

# Features Designed for Your Success




## Biocompatibility

Lumen X+ Photolinks are biocompatible, so cells can be used with printed constructs. When using GelMA, cells can even be mixed into the Photolink. The built-in heater keeps GelMA liquefied and improves cell viability within the Photolink.



## Open Materials Platform

The Lumen X+ allows users to develop and use their own materials without workarounds or extra fees, opening the door for the development of materials with unique properties or for novel tissue engineering applications.




## Flexibility

Combining the Lumen X+ with CELLINK's BIO X™ lets users multiply the benefits of each system's state-of-the-art capabilities. For example, the BIO X can print living cells within a structure fabricated on the Lumen X+ to strengthen work in applications like multimaterial research.



## Speed

By curing entire layers simultaneously, the Lumen X+ can build structures **10 mm** tall in GelMA in 30 minutes (up to **50 times** faster than other printing methods). This translates to better cell viability and higher throughput when model building.



## Isotropy

Compared to extruded scaffolds, Lumen X+ scaffolds are significantly more isotropic, allowing users to control mechanical properties with geometry in all dimensions. Users can also build unique structures, such as Schwarz lattices or auxetic structures.



## Clarity

The photo-absorbing dye that gives the Photolinks their color will wash out of printed structures in a matter of hours, allowing structures to be imaged via bright-field or fluorescence imaging techniques.



## Resolution

DLP technology coupled with Volumetric Photolinks allow the Lumen X+ to build watertight channels in hydrogels with greater consistency and precision than extrusion. This allows the Lumen X+ to create microfluidic lab-on-a-chip devices, strengthening work in:

- Disease pathology
- Drug screening
- Tissue engineering
- And more!



## Intricacy

Gentle separation forces and material strength allow the Lumen X+ to build intricate scaffold geometries that include porosity and vasculature in X, Y and Z dimensions. Scaffolds can now have geometry that is far more biomimetic when engineering tissue such as trabecular bone.

# PhotoInks and Consumables



## PEGDA

PEGDA PhotoInk is an advanced biocompatible and nonbiodegradable bioink designed specifically for the Lumen X+.

It is ideal for bioprinting soft, gas-permeable microfluidic devices with intricate vascular architectures and for building macroporous scaffolds with struts >600 µm. The printed hydrogel will be mostly transparent with a stiffness closer to that of kidney fat.



## PEGDA500

PEGDA500 PhotoInk is an advanced biocompatible and nonbiodegradable bioink designed specifically for the Lumen X+. It is ideal for bioprinting microfluidic devices and lattice structures with struts >200 µm.

The printed hydrogel will be optically translucent, stiffer than cartilage and strong enough to permit the forming of thin walls and small channels. It can be used for drug delivery and constructs that do not require optical transparency.



## PEGDA Start

PEGDA Start PhotoInk is an excellent starter bioink for learning to print with the Lumen X+. It is ideal for rapidly testing new designs, printing microfluidic devices and building tissue lattice structures with struts >200 µm.

The printed hydrogel is optically translucent and does not swell substantially in water. While its stiffness resembles that of bone, it is not as durable.



## GeIMA

GeIMA PhotoInk is an optimized gelatin-based biodegradable bioink designed specifically for the Lumen X+. Because fabricated hydrogels can be cured with little-to-no impact on cell viability, the GeIMA PhotoInk can be mixed with cell pellets. It can also resolve intricate vascular networks and channels that offer endothelial and epithelial cells the essential properties of their native environments. Lumen X+'s built-in heating function is crucial for generating complex GeIMA-based hydrogels.




## Light Meter

Light Meter contains a probe specifically designed for the Lumen X+'s biocompatible 405 nm wavelength. It can be used to precisely measure light intensity and set the ideal power output before printing with the Lumen X+. Although it is not necessary to measure the light intensity between every print, we recommend checking power output at the start of each print session.



## Lumen X+ Vats

PDMS Dishes are lined with a proprietary silicone formula to enable the gentle separation of cured PhotoInk layers while printing with the Lumen X+. Sterile packaging is available for bioprinting with mammalian or bacterial cells, while nonsterile vats can be rinsed with 70% IPA or ethanol and used for multiple prints. When printing larger objects, a fresh vat is highly recommended to optimize printability.





# LUMEN X<sup>+</sup>

**CELLINK**   
A BICO COMPANY

| **Volumetric** 

## Contact

Email: [sales@cellink.com](mailto:sales@cellink.com)

US phone: (+1) 833-235-5465

European phone: +46 31-128 700

Website: [www.cellink.com](http://www.cellink.com)

Scan to learn more



## Office Locations

Blacksburg  
*USA*

Gothenburg  
*Sweden*

Freiburg  
*Germany*

Lyon  
*France*

Brighton  
*UK*


Kyoto  
*Japan*

Stuttgart  
*Germany*

Boston  
*USA*








## Lumen X+ Build Platform

Build Platform holds prints for the duration of the build. Its small size minimizes the amount of Photolnk required per build, conserving material and cells alike. Each one is precisely machined, so that platforms can be swapped quickly and easily with little downtime between prints. Offered in glass for better adhesion to hydrogel constructs and in metal for better adhesion to resin-based constructs.



## Technical Specifications

Dimensions (L x W x H)	43 x 24 X 41 cm (17 x 9.5 x 16.5 in)
Power supply	AC 100-120V, 50/60Hz, 10A or AC 200-240V, 50/60Hz, 5A
Weight	10 kg (22 lbs.)
Projected image	1280 x 800 pixels
Pixel resolution (XY)	50 $\mu$ m
Z-precision (motor-driven)	5 $\mu$ m
Max build volume	65 x 40 x 50 mm
Projected light wavelength	405 nm
Intensity range	10–30 mW/cm <sup>2</sup>
Deviation from mean	<1%
Electrical power input	100–265 VAC, 50–60 Hz, 100 W
Compatible file type	STL (stereolithography file)
Connectivity	USB-A, USB-C